

3M™ Overhead Projector

Model 1865

Brilliant Presentation Tool

A brilliant presentation tool, the 3M™ Overhead Projector Model 1865 comes with an articulating wide-angle closed singlet lens and 3,600 to 4,300 lumens of light for bright, big-screen images. A unique color-tuning dial eliminates blue or brown corners, two different lamp settings switch between high and low for crisp black-and-white text and vivid color images, hushquiet fan reduces noise for more enjoyable presentations, and convenient carrying handle and fold-down post adds optimal portability and storability. Features also include thermal-protection circuit that disconnects power to lamp in the unlikely event that the projector overheats, practical lamp ejector that makes replacing lamps simple, lamp interrupt switch that shuts off power to lamp when changing lamps to prevent premature lamp failure, and handy power-cord wrap. The 3M Overhead Projector Model 1865 comes with a five-year warranty on all parts and labor.



KEY FEATURES

- > Articulating wide-angle closed singlet lens shows bright, big-screen images.
- > High-to-low device switches from 3,600 to 4,300 lumens for black-and-white and color transparencies.
- > Dimmer switch conserves lamp life.
- > Handy lamp changer makes switching lamps easy.
- > Convenient carrying handle and fold-down post provide optimal portability and storability.
- > Power-cord wrap eliminates tangled electrical cord.
- > Practical lamp ejector makes replacing lamps a simple task.
- > Five-year warranty on all parts and labor. Please see product packaging for details of warranty terms.

ORDER NUMBER: X0-0038-0718-7 (former#: 78-9236-6604-0)

OPTIONAL ACCESSORIES: Replacement lamp, roller attachment, roller-attachment film, and dust cover

TECHNICAL SPECIFICATIONS

Specifications subject to change.

OPTICAL PERFORMANCE

- > Head: **Articulating, closed singlet** (one element) wide angle lens
- > Illumination: **4,300 ANSI lumens typical** (3,600 lumens -- low setting)
- > Design: **Transmissive** with folded optical system
- > Stage aperture: **267 mm x 267 mm** (10.5 inches x 10.5 inches)
- > **Color-tuning dial**

LAMP DESCRIPTION

- > **Lamp ejector**
- > **Lamp changer**
- > Lamp Type: **FXL** (82 volts, 410 watts)
- > Lamp Life: **40 hours** (high setting), **80 hours** (low setting) using Model 1865

PHYSICAL CHARACTERISTICS

- > **Internal high/low switch**

ELECTRICAL FEATURES

- > **Hush-quiet fan**
- > Power-cord length: **4.6 m** (15 feet)
- > **Power-cord wrap**

MECHANICAL

- > **Carrying handle**
- > **Fold-down post**

**Ask
about 3M
LAMPS!**

1.800.328.1371

WWW.3M.COM/meetings

“Wherever there’s a great meeting, you’ll find 3M.”™

Visual Systems Division
Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Canada
P.O. Box 5757
London, Ontario, Canada
N6A 4T1

3M Mexico, S.A. de C.V.
Apartado Postal 14-139
Mexico, D.F. 07070
Mexico

3M Presentation Solutions