



**SPECIFICATION DATA**

**SUGGESTED SPECIFICATIONS:** \_\_\_\_\_ projection screen(s), \_\_\_\_\_ (H) x \_\_\_\_\_ (W), operated by a system of ropes and pulleys. To have a straight, rigid tubular metal header, 3" in diameter. Top of fabric shall be formed into a pocket into which header shall be inserted. Three 3" wide double "C" type clamps of high tensile strength cast aluminum shall be secured to header for hanging. Center clamp shall be furnished with a turnbuckle for taking out any center sag. Fabric shall be flame retardant and mildew resistant with Glass Beaded or Matte White picture surface with black masking borders standard on fiberglass fabric. Bottom roller shall be of rigid metal, a minimum of 3" in diameter for screens with a width of less than 20' x 20' and a minimum of 5" for screens 20' x 20' and over. Fabric shall be securely fastened to roller. The roller shall be 24" longer (30" on 30' x 30') and the header 6" longer than the width of the fabric. Ends of tubular header shall be protected with cast aluminum end caps fitted with internal nylon pulleys. Two 3/8" diameter polyester solid braid cord ropes shall be attached to the roller, run through brass protected opening in header, through the pulleys and fastened with a cable clamp at the desired drop. There shall be sufficient rope to provide one or more complete turns on the roller when the screen is in the "UP" position and provide a free end equal to the height of the screen when screen is in the "DOWN" position. (Note: If ropes are to run across ceiling or stage and down wall, specify exact amount of extra rope required.)

**Matte White and Glass Beaded:** Horizontal seams required when both dimensions exceed 8 feet.

**DIMENSIONS**

Sizes		Overall Header		Overall Bottom		Top of Clamp to Roller Bottom in Up Position (Appr.)		Approx. Ship. Wt.	
H x W	Cm	In.	Cm	In.	Cm	In.	Cm	Lbs.	Kg
10'6" x 14'	320.0 x 426.7	175-1/2"	446	192"	488	10"	25	148	67
14' x 14'	426.7 x 426.7	175-1/2"	446	192"	488	10"	25	164	74
6' x 16'	182.9 x 487.7	199-1/2"	507	216"	549	10"	25	145	66
12' x 16'	365.8 x 487.7	199-1/2"	507	216"	549	10"	25	161	73
16' x 16'	487.7 x 487.7	199-1/2"	507	216"	549	10"	25	215	98
7' x 18'	213.4 x 548.6	223-1/2"	568	240"	610	10"	25	160	73
13'6" x 18'	411.4 x 548.6	223-1/2"	568	240"	610	10"	25	245	111
18' x 18'	548.6 x 548.6	223-1/2"	568	240"	610	10"	25	416	189
15' x 20'	457.2 x 609.6	247-1/2"	629	264"	671	10"	25	562	255
20' x 20'	609.6 x 609.6	247-1/2"	629	264"	671	12"	30	575	261
18' x 24'	548.6 x 731.5	295-1/2"	751	312"	792	12"	30	674	442
24' x 24'	731.5 x 731.5	295-1/2"	751	312"	792	12"	30	690	313
21' x 28'	640.1 x 853.4	343-1/2"	872	360"	914	12"	30	787	357
28' x 28'	853.4 x 853.4	343-1/2"	872	360"	914	12"	30	800	363
22'6" x 30'	685.8 x 914.4	367-1/2"	933	384"	975	12"	30	850	386
30' x 30'	914.4 x 914.4	367-1/2"	933	390"	991	12"	30	880	399

Specifications subject to change without notice.

Distance between hanger eyes can be calculated for any size screen. The turnbuckle is centered on fabric and clamped to top header. The other two clamps are located 6" in from each side of fabric. Other sizes (not exceeding 30' x 30') on request.



**PLEASE MARK APPROPRIATE SELECTIONS:**

Select size from chart above.

Select viewing surface:

- Matte White
- Glass Beaded

**Options:**

- No borders (Black masking borders standard)
- Extra Drop - Available in Black or White fabric. Maximum total drop 30'.
- Extra Rope. Specify length required \_\_\_\_\_.

Project: \_\_\_\_\_

Architect: \_\_\_\_\_

Phone: \_\_\_\_\_

Contractor: \_\_\_\_\_

Phone: \_\_\_\_\_

Supervisor: \_\_\_\_\_

Phone: \_\_\_\_\_

Supplier: \_\_\_\_\_

Date: \_\_\_\_\_

Revised: \_\_\_\_\_