

Distributed by:

Headset Boom Microphone

Model 3064AV (Beige)



- **IBM and Mac compatible (excluding iMac)**
- **Electret mic on flexible gooseneck**
- **On-line volume control**
- **8 foot cord with 3.5mm mini plugs**
- **Adjustable headband**
- **Replaceable leatherette ear cushions**

An ideal companion for today's digital classroom, these headphones are compact, lightweight, and adjustable.

Perfect for use with computer labs, CD players, sound blasters, stereo systems, video players, and cassette recorders, they feature an omni-directional electret microphone with a wind screen.

"Project Intercept"

Please contact us immediately if you experience any difficulties with your headphone. Our "Project Intercept" customer service program will quickly repair or replace items under warranty. Simply contact us via phone 1-800-722-0500 or email rilane@califone.com.

Visit our website at www.califone.com to learn more about the complete line of *Califone*® headphones and other audio products including: Public address systems, wireless microphone systems, group listening centers, boomboxes, DVD/CD/cassette recorders / players, cordless headphone systems and computer peripherals. We are proud of offering more than fifty-five years of *Powerful Sound Presentation Solutions*™ for portable audio applications, with your satisfaction as our first priority.

Or, give us a call at 800-722-0500, and experience the *Califone* difference today!

Specifications

Headphone

| | |
|--------------------|---|
| Diaphragm | 27mm Mylar |
| Magnet | Cobalt |
| Impedance | 25 Ohms \pm 5 Ohms |
| Frequency Response | 20-20,000 Hz |
| Sensitivity | 100dB SPL \pm 3dB at 1kHz |
| Max Input | 100 milliwatts |
| Input Connection | 3.5mm, black jacketed, nickel plated stereo |

Cord

8 feet with attached volume control

Microphone

| | |
|--------------------|---|
| Type | Electret condensor with wind shield |
| Directivity | Omni-directional |
| Sensitivity | 60dB \pm 3dB at 1kHz |
| Frequency Response | 20-16,000 Hz |
| Impedance | 2,000 Ohms \pm 15% |
| Operating Voltage | Nominal +3V; accepts 1.5V-10V |
| Output Connection | 3.5mm, red jacketed, nickel plated stereo |



Califone® International, Inc. • 800.722.0500 • www.califone.com